




CTSAD003.2

Audi Steering Wheel Control Interface



Vehicle Application

Audi A3 (8P) 2003 - 2005
Audi A4 (8E, B6, B7) 2001 - 2008
Audi TT (8N) 2003 - 2006

Key Features

- Retains Steering Wheel Controls
- Retains BOSE/Half Amplified Systems
 - Retains OEM Phone Buttons
- Provides Speed Pulse, Park Brake, Reverse Gear and Amp Remote Outputs

www.connects2.com

Designed and
Engineered
in the UK. 

ABOUT THIS PRODUCT

CTSAD003.2

CAN-Bus Steering Wheel Control Interface for Audi vehicles with Concert, Symphony or Chorus original stereos and Quadlock (40 Way) connectors. Supports BOSE and half amplified systems via RCA connections. Aftermarket stereo must have RCA audio out connectors.

Note: For Sony Head Unit Installation

If a Sony head unit is being installed in the vehicle, open the interface box and ensure that DIP switch 4 on the PCB board is set to 'OFF'

WIRING COLOUR CODES

Purple	Right Rear Speaker +	Yellow	Permanent 12V
Purple/Black	Right Rear Speaker -	Black	Ground
Green	Left Rear Speaker +	Red	Ignition 12V
Green/Black	Left Rear Speaker -	Orange	Illumination
Grey	Right Front Speaker +	Pink	Speed Pulse
Grey/Black	Right Front Speaker -	Green	Park Brake
White	Left Front Speaker +	Purple/White	Reverse Gear
White/Black	Left Front Speaker -	Blue*	Amp Remote

*The blue 'Amp Remote' flying wire must be connected in order to provide amplifier sound through the OEM speakers

PRIOR TO INSTALLATION

*Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources. Please ensure that the correct tools are using during the installation to avoid damage to the vehicle or product. **Connects2 can not be held responsible for the installation of this product.***

TECHNICAL SUPPORT

Connects2 Ltd. want to provide a fast and suitable resolution to any problems encountered during installation of this product. To get in touch with our dedicated technical support team, please fill in a ticket at support.connects2.com and provide as much information as possible.

FOLLOW US ON SOCIAL MEDIA
for all the latest updates



[/CONNECTS2](#)
Watch us on YouTube



[/CONNECTS2](#)
Like us on facebook



[CONNECTS2LTD](#)
Follow us on instagram



[@CONNECTS2](#)
Follow us on twitter




[CONNECTS2LTD](#)
Follow us on linkedin



[CONNECTS2BLOG.COM](#)
Follow our blog on wordpress

FITTING GUIDE

1. Remove and disconnect the original head unit.
2. Connect the 12 way molex connector of the head unit patch lead (supplied separately) to the interface.




3. Connect the opposite end of head unit patch lead to the head unit steering wheel control input on the back of the aftermarket head unit.

NB: This may be a 3.5mm jack plug or a wire input depending upon the head unit brand being fitted. Please see the head unit installation manual for further information on where to connect.

Important: This step must be completed before connecting power to the interface. Failure to so do may result in no steering wheel control function.



4. Connect the 14 way molex connector to the interface



5. Connect the male power/speaker ISO harness to the female power/speaker ISO harness from the aftermarket head unit. For aftermarket head units without an ISO connector, please refer to "Wiring Colour Codes" on Pg. 2.



FITTING GUIDE

6. Connect the RCA connectors to the back of the aftermarket stereo to retain OEM amplifier (Note: the blue 'Amp Remote' flying wire must also be connected to the vehicle in order to provide amplifier sound through the OEM speakers).

7. Connect the female vehicle specific connectors on the harness to the male vehicle connector from the vehicle. Test head unit for correct operation and reassemble the dashboard.

STEERING WHEEL CONTROL FUNCTIONALITY

